

Portofino Chevron 90

25-02-2026

technical data sheet

EN

Product specifications

Three-layer parquet	EN 13489	DoP PQ2021-5
Size	Plank	90 x 510 x 14(3) mm
	Box	16 planks / 0.7344 m ² / 5.5 kg
	Pallet	80 boxes / 58.752 m ² / 456 kg
Density	EN 323	± 650 kg/m ³
Installation		Tongue & Groove
Top layer		European oak (Quercus robur)
Core		Poplar (Populus deltoides)
Counter balance		Poplar (Populus deltoides)
Grading		Rustic A+
Texture		Slightly Brushed
Bevel		4V
Gloss level at 60°		4-6 %
Finishing		UV Oil
Warranty conditions	Residential warranty	20 years
	Commercial warranty	upon request
Use class	EN 13489	Class 23 Heavy domestic use



Product properties

property		test method	min. req.	result
Indoor air certifications				REACH, A
Reaction to fire		EN 13501-1		Dfl-s1
Slip resistance		CEN/TS 15676		Dry 54
Formaldehyde emission		EN 717-1	≤ 0.124 mg/m ³	E1
Pentachlorophenol content		CEN/TR 14823	< 5 ppm	Does not contain pentachlorophenol
Underfloor heating		EN 12664	R < 0.15 m ² K/W	R = 0,10 m ² K/W OK (max +28°C) + glued
Biological durability				Class 1

Cleaning and maintenance instructions: www.lamett.eu



EN)

Texture	Slightly Brushed
Grading	Rustic
Colour variation	Low
Sound knots	≤ 2 per plank; Ø ≤ 20 mm
Unsound knots	≤ 2 per plank; Ø ≤ 15 mm
Sapwood	max 25 mm width, ≤ 20% of width
End crack	Not allowed
Surface crack	Not allowed
Insect hole	Not allowed
Decay	Not allowed
Blue/yellow stain	Not allowed
Sound heart	Not allowed
Machine marks	Not allowed

