

Orvieto Click 190

technical data sheet

EN

Product specifications

Multilayer parquet	EN 13489	DoP PQ2024-13
Size	Plank	190 x 680-1900 x 14(3) mm
	Box	8 planks / 2,888 m ² / 24,1 kg
	Full planks	6
	Pallet	45 boxes / 129,96 m ² / 1106,5 kg
Density	EN 323	± 536 kg/m ³
Installation		Drop Lock
Top layer		European oak (Quercus robur)
Core		Spruce (Picea abies)
Counter balance		Spruce (Picea abies)
Grading		Rustic B+
Texture		Distressed
Bevel		4V
Gloss level at 60°		5-7 %
Finishing		Natural Oil
Warranty conditions	Residential warranty	20 years
	Commercial warranty	upon request
Use class	EN 13489	Class 23 Heavy domestic use



Empty fields indicate variations between the colors within the collection. Please refer to the table below for specific data per color.

Variables within the collection

Article Code	Colour	Finish	Texture
ORV 190 CL-1007	1007-Prosecco	Oil	Distressed
ORV 190 CL-1009	1009-Heritage	Oil	Distressed
ORV 190 CL-1011	1011-Antique	Oil	Distressed
ORV 190 CL-110	110 - Natural	Oil	Distressed

Orvieto Click 190

technical data sheet

EN

Product properties

property		test method	min. req.	result
Indoor air certifications/labels				A
Reaction to fire		EN 13501-1		Dfl-s1
Slip resistance		CEN/TS 15676		USRV 42
Pentachlorophenol content		CEN/TR 14823	< 5 ppm	Does not contain pentachlorophenol
Underfloor heating		EN 12664	R < 0.15 m²K/W	R = 0.12 m²K/W OK (max +28°C) + glued
Biological durability				Class 1

Formaldehyde emission

CE-Marking - EN 14342		EN 717-1	≤ 0.124 mg/m³	E1
REACH Annex XVII Entry 77		EN 717-1	< 0.062 mg/m³	0.025 mg/m³



Orvieto Click 190

Rustic B+
EN

Grading description

Texture	Distressed
Grading	Very rustic
Colour variation	High
Sound knots	$\varnothing \leq 70$ mm
Unsound knots	≤ 3 per plank, $\varnothing \leq 60$ mm
Sapwood	$\leq 30\%$ of the width
End crack	$\leq 5 \times 200$ mm
Surface crack	$\leq 4 \times 300$ mm
Insect hole	Allowed
Decay	Allowed
Blue/yellow stain	Allowed
Sound heart	Allowed; closed pith
Machine marks	Not allowed



This picture is an indication of the grading as described.

Grading description – 2 criteria

Knots

Scale from (rigid) parquet without knots up to planks with more and larger knots



Colour variation

From little colour variation/sapwood to bigger colour variation/sapwood



Cleaning and maintenance instructions: www.lamett.eu