

New York 190 PEFC

technical data sheet






EN

Product specifications

Three-layer parquet	EN 13489	DoP PQ2024-13
Size	Plank	190 x 680-1900 x 14(3) mm
	Box	6 planks / 2,888 m ² / 21,66 kg
	Full planks	5
	Pallet	45 boxes / 129,96 m ² / 1005 kg
Density	EN 323	± 500 kg/m ³
Installation		Drop Lock
Top layer		European oak (Quercus robur)
Core		Pine (Radiata pine)
Counter balance		Pine (Radiata pine)
Grading		Rustic A+
Texture		Slightly Brushed
Bevel		4V
Gloss level at 60°		5-7 %
Finishing		Matt Lacquer
Warranty conditions	Residential warranty	20 years
	Commercial warranty	upon request
Use class	EN 13489	Class 23, Class 31 Moderate commercial use



Product properties

property	test method	min. req.	result
Indoor air certifications			REACH, A
Reaction to fire	 EN 13501-1		Dfl-s1
Slip resistance	 CEN/TS 15676		USRV 42
Formaldehyde emission	 EN 717-1	≤ 0.124	E1
Pentachlorophenol content	 CEN/TR 14823	< 5 ppm	Does not contain pentachlorophenol
Underfloor heating	 EN 12664	R < 0.15 m ² K/W	R = 0.11 OK (max +28°C) + glued
Biological durability			Class 1

Cleaning and maintenance instructions: www.lamett.eu



New York 190 PEFC

Rustic A+

EN

Grading description

Texture	Slightly Brushed
Grading	Rustic
Colour variation	Low - Medium
Sound knots	Allowed unlimited; $\varnothing \leq 20$ mm
Unsound knots	≤ 2 per plank; $\varnothing \leq 12$ mm
Sapwood	Allowed unlimited if colour matches plank
End crack	Allowed; filled; width ≤ 50 mm; length ≤ 100 mm
Surface crack	Allowed; filled; width ≤ 50 mm; length ≤ 150 mm
Insect hole	Not allowed
Decay	Not allowed
Blue/yellow stain	Not allowed
Sound heart	Allowed unlimited
Machine marks	Not allowed



This picture is an indication of the grading as described.

Grading description

Scale from (rigid) parquet without knots up to planks with more and larger knots



From little colour variation/sapwood to bigger colour variation/sapwood

