







technical data sheet

EN

Product specifications

Three-layer parquet	EN 13489	DoP PQ2024-13
Size	Plank	190 x 680-1900 x 14(3) mm
	Box	8 planks / 2,888 m ² / 24,1 kg
	Full planks	6
	Pallet	45 boxes / 129,96 m ² / 1106,5 kg
Density	EN 323	± 536 kg/m ³
Installation		Tongue & Groove
Top layer		European oak (Quercus robur)
Core		Spruce (Picea abies)
Counter balance		Spruce (Picea abies)
Grading		Rustic B+
Texture		Slightly Brushed
Bevel		4V
Gloss level at 60°		5-7 %
Finishing		UV Matt Lacquer
Warranty conditions	Residential warranty	20 years
	Commercial warranty	upon request
Use class	EN 13489	Class 23 Heavy domestic use 

Product properties

property	test method	min. req.	result
Indoor air certifications			REACH, A
Reaction to fire	 EN 13501-1		Dfl-s1
Slip resistance	 CEN/TS 15676		USRV 42
Formaldehyde emission	 EN 717-1	≤ 0.124 mg/m ³	E1
Pentachlorophenol content	 CEN/TR 14823	< 5 ppm	Does not contain pentachlorophenol
Underfloor heating	 EN 12664	R < 0.15 m ² K/W	R = 0,12 m ² K/W OK (max +28°C) + glued
Biological durability			Class 1

Cleaning and maintenance instructions: www.lamett.eu



Osaka 190

19-01-2026

Rustic B+

EN

Grading description

Texture	Slightly Brushed
Grading	Very rustic
Colour variation	High
Sound knots	Allowed unlimited
Unsound knots	Ø ≤ 80 mm
Sapwood	≤ 30% of width - coloured to same colour as planks
End crack	≤ 10*300 mm
Surface crack	≤ 6*300 mm
Insect hole	Wormhole allowed, max. 10
Decay	Allowed
Blue/yellow stain	Allowed
Sound heart	Allowed; closed pith
Machine marks	Not allowed



This picture is an indication of the grading as described.

Grading description

Scale from (rigid) parquet without knots up to planks with more and larger knots



From little colour variation/sapwood to bigger colour variation/sapwood

