

technical data sheet

EN

Product specifications

Rigid Core SPC	EN 15102	DoP WPB2026
Size	Tile	592 x 1184 x 4 mm
	Box	4 tiles / 2.804 m ² / 23.1 kg
	Pallet	31 boxes / 86.924 m ² / 740 kg
Density	EN ISO 23996	± 2050 kg/m ³
Installation		Tongue & Groove - 4-sided
Bevel		Painted bevel
Different tiles		18
Texture		Stone Structure
Finish		Standard Gloss (5-8%)
Coating		Antimicrobial UV
Surface layer		Not applicable
Warranty conditions	Residential warranty	15 years
	Commercial warranty	10 years

Product properties

property		test method	min. req.	result
Reaction to fire		EN 13501-1		B-s2, d0
Dimensional stability		EN ISO 23999	≤ 0.15 %	0.03 %
UV resistance		EN ISO 105-B02	≥ 6	6
Scratch resistance		EN 16094	≤ MSR-A5 / ≤ MSR-B5	MSR-A1 MSR-B4
Stain resistance		EN 438-2		Group 1 and 2 : Grade 5 Group 3 : Grade 5
Thermal resistance		EN 12664	< 0.15 m ² K/W	0.039 m ² K/W

technical data sheet



Environment			
property	test method	min. req.	result
Indoor air certifications			Phthalate free, REACH, IAC Gold, A+
TVOC (28 days)	EN 16516		< 5 µg/m³
Recycled content			29 %
Formaldehyde emission			
CE-Marking - EN 15102	EN 12149	≤ 0.120 mg/m³	ND
REACH Annex XVII	EN 16516	< 0.080 mg/m³	0.003 mg/m³
Release of heavy metals & specific elements	EN 12149		ND
Release of vinyl chloride monomer	EN 12149		ND

Cleaning and maintenance instructions: www.lamett.eu

