

technical data sheet






EN

Product specifications

Multi-Ply Oak wood flooring	EN 13489 (Free Class)	DOP PQ2022-9
Dimensions	Plank	600-1900 x 150 x 10/ 3 mm
	Box	10 planks / 2,85 m ² / 20 kg
	Nested lengths	8 full planks (Max. 2 min. 600 mm)
	Pallet	54 boxes / 153.90 m ² / 1080 kg
Density	EN ISO 23996	+/- 650 kg/m ³
Installation	ISO 24334	T&G (glued)
Top layer		3 mm European oak (Quercus Robur)
Grading		Rustic AB+
Surface		Medium brushed
Bevel		Bevel 4V
Gloss level	60°	5-10%
Finishing		Matt lacquer
Warranty conditions	Residential use	20 years
	Commercial use	upon request
Application	EN 13489	Class 23



Product properties

Property	Test method	min. req.	result
Indoor air certifications			A, REACH
Fire resistance	 EN 13501-1		Dfl-S1 (CWFT)
Slip resistance	 EN 13893		DS (≥ 0.30)
Formaldehyde emission	 EN 717-1	≤ 0.124 mg/m ³	E1
Pentachlorofenol content	 EN 12673	< 5 ppm	< detectable limit
Underfloor heating	 EN 12667	R < 0.15 m ² K/W	R = 0,06 m ² K/W OK (max +28°C) + glued
Biological durability			Class 1

Cleaning and maintenance instructions: www.lamett.eu



Rustic AB+

EN

Grading description

Texture	Medium brushed
Grading	Rustical
Colour variation	High
Sound knots	Permitted; $\varnothing < 50\text{mm}$
Unsound knots	Permitted; $\varnothing < 30\text{mm}$
Bark	Not allowed
Sapwood	$< 300\text{mm}$ length, $< 20\text{mm}$ width
End crack	Allowed
Surface crack	
Insect hole	Not allowed
Decay	Not allowed
Blue/yellow stain	Allowed limited
Sound heart	Not allowed
Machine marks	Not allowed



This picture is an indication of the grading as described.

Grading description — 2 criteria

Knots

Scale from (rigid) parquet without knots up to planks with more and larger knots



Colour variation

Scale from (rigid) parquet without knots up to planks with more and larger knots

