

# Vienna 120

## technical data sheet

EN

### Product specifications

|                     |                      |                                                                                      |
|---------------------|----------------------|--------------------------------------------------------------------------------------|
| Solid parquet       | EN 13226             | DoP MAS2021                                                                          |
| Size                | Plank                | 120 x 400-1800 x 15 mm                                                               |
|                     | Box                  | 7 planks / 1.512 m <sup>2</sup> / 16.5 kg                                            |
|                     | Full planks          | 1                                                                                    |
|                     | Pallet               | 49 boxes / 74.088 m <sup>2</sup> / 828.5 kg                                          |
| Density             | EN 323               | ± 650 kg/m <sup>3</sup>                                                              |
| Installation        |                      | Tongue & Groove                                                                      |
| Core                |                      | European oak (Quercus robur)                                                         |
| Grading             |                      | Rustic AB+                                                                           |
| Texture             |                      |                                                                                      |
| Bevel               |                      | 4V                                                                                   |
| Gloss level at 60°  |                      | 5-7 %                                                                                |
| Finishing           |                      | UV Oil                                                                               |
| Warranty conditions | Residential warranty | 30 years                                                                             |
|                     | Commercial warranty  | upon request                                                                         |
| Use class           | EN 13226             | Class 23, Class 33                                                                   |
|                     |                      | Heavy commercial use                                                                 |
|                     |                      |  |

### Product properties

| property                  |                                                                                     | test method  | min. req.                   | result                             |
|---------------------------|-------------------------------------------------------------------------------------|--------------|-----------------------------|------------------------------------|
| Indoor air certifications |                                                                                     |              |                             | REACH, A+                          |
| Reaction to fire          |  | EN 13501-1   |                             | Cfl-s1                             |
| Slip resistance           |  | CEN/TS 15676 |                             | USRV 63                            |
| Formaldehyde emission     |  | EN 717-1     | ≤ 0.124                     | E1                                 |
| Pentachlorophenol content |  | CEN/TR 14823 | < 5 ppm                     | Does not contain pentachlorophenol |
| Underfloor heating        |  | EN 12664     | R < 0.15 m <sup>2</sup> K/W | R = 0.09<br>OK (max +28°C) + glued |
| Biological durability     |                                                                                     |              |                             | Class 1                            |

Cleaning and maintenance instructions: [www.lamett.eu](http://www.lamett.eu)



# Vienna 120

Rustic AB+

EN

## Grading description

|                   |                                 |
|-------------------|---------------------------------|
| Texture           |                                 |
| Grading           | Rustic                          |
| Colour variation  | Medium                          |
| Sound knots       | $\varnothing \leq 50\text{mm}$  |
| Unsound knots     | $\varnothing \leq 30\text{mm}$  |
| Sapwood           | Max 1/3 of plank                |
| End crack         | Length max. of 5 cm; width 1 mm |
| Surface crack     | Width 1 mm, no limit in length  |
| Insect hole       | Not allowed                     |
| Decay             | Not allowed                     |
| Blue/yellow stain | Not allowed                     |
| Sound heart       | Allowed                         |
| Machine marks     | Not allowed                     |



This picture is an indication of the grading as described.

## Grading description

Scale from (rigid) parquet without knots up to planks with more and larger knots

From little colour variation/sapwood to bigger colour variation/sapwood

