

Maintenance kit

oiled parquet

The maintenance kit consists of:

1 liter Natural Soap | 250 ml Oil Refreshing Soap

Natural Soap is a purpose-made quality soap, which due to its nourishing properties quickly closes the pores of the wood and protects against dirt and penetration of liquids. Available in Natural and White.

Oil Refreshing Soap may be used for all oiled surfaces and is especially suitable for the yearly maintenance of wood surfaces. Available in Natural and White.



10 tips for optimal care

1. Clean the floor regularly with a vacuum cleaner or soft broom; particles of dirt and grit that are left behind can damage the surface of the floor.
2. Place doormats at exterior doors.
3. Place beige, felt floor protectors under chair and table legs; do not use coloured floor protectors!
4. Avoid wearing damaged or worn stiletto heels.
5. Place a protective mat under chairs with wheels.
6. Remove stains immediately with a well-wrung cloth. Worn-in stains are difficult to remove.
7. Never use too much water when mopping; instead use a well-wrung floor cloth. Never clean the floor with pure water; always use a product for the maintenance of an oiled parquet. Do not use traditional cleaning products. Microfibre cloths can damage your floor over time.
8. Place a protective dish under flowerpots. Do not place your buckets directly on the floor, but on a dry mop.
9. Do not drag heavy objects across the floor; lift them up to avoid scratches.
10. Be careful with open windows - a rain shower can damage the floor.

Air humidity level

In the case of problems with a wooden floor, the cause is too low air humidity in 90% of the cases. With a wooden floor, always ensure that there is sufficient air humidity in the house. **The ideal level is between 40 and 55%.** Too low air humidity can cause irreparable cracks, rising of planks,... So it is certainly worthwhile to keep an eye on this with an air humidity meter and, if necessary, provide a humidifier. Especially in winter you have to be alert.

Maintenance kit

oiled parquet

First treatment after installation

After installation we advise a first cleaning with Woca Oil Refreshing Soap.

1. Shake the container carefully. The floor must be free from dust before treatment.
2. Clean the floor with 125 ml Oil Refresher mixed into 5 liter of cold water.
3. Treat with a light wrung floor cloth or mop lengthwise of the floor. Immediately afterwards, dip floor cloth or mop into mixture and wipe the floor with hard wrung floor cloth or mop again lengthwise of the wood.
4. Leave the floor to dry for approx 2 hours before use.

14 days later you can start the maintenance with the Natural Soap.

(Two-)weekly cleaning with the Natural Soap

The Natural Soap is ideal for the cleaning and maintenance of all oiled, UV oiled or soaped wood surfaces.

1. Shake the Natural Soap carefully before use.
 2. 125 ml Natural Soap is mixed into 5 liter of cold water.
 3. Always mop the floor with soap water on hard-wrung mop or cloth in order to reestablish the protective Natural soap film.
 4. Leave the floor to dry for approx 5-10 minutes before use.
-



Annual cleaning with the Oil Refreshing Soap

This Oil Refreshing Soap combines efficient cleaning with re-oiling as addition oil is penetrating into the wood of the floor forming a mat protective layer in the surface. Oiled floors should be regularly maintained – normally once a year, but more often when it comes to floors exposed to extremely hard wear.

1. Shake the container carefully. The floor must be free from dust before treatment.
2. Clean the floor with 125 ml Oil Refresher mixed into 5 liter of cold water.
3. Treat with a light wrung floor cloth or mop lengthwise of the floor. Immediately afterwards, dip floor cloth or mop into mixture and wipe the floor with hard wrung floor cloth or mop again lengthwise of the wood.
4. Leave the floor to dry for approx 2 hours before use.

