

technical data sheet

EN

Product specifications

Rigid Core SPC	EN 15102	DoP WPC2026
Size	Tile	592 x 1184 x 4 (0.25mm PET) mm
	Box	4 tiles / 2.804 m ² / 23.1 kg
	Pallet	31 boxes / 86.924 m ² / 740 kg
Density	EN ISO 23996	± 2100 kg/m ³
Installation		Tongue & Groove - 4-sided
Bevel		Non Bevelled
Different tiles		18
Texture		Marble Structure
Finish		High Gloss 105%
Coating		Not applicable
Surface layer		0.25 PET film
Warranty conditions	Residential warranty	15 years
	Commercial warranty	10 years

Product properties

property		test method	min. req.	result
Reaction to fire		EN 13501-1		C-s2, d0
Dimensional stability		EN ISO 23999	≤ 0.15 %	0.03 %
UV resistance		EN ISO 105-B02	≥ 6	6
Scratch resistance		EN 16094	≤ MSR-A5 / ≤ MSR-B5	MSR-A1 MSR-B4
Stain resistance		EN 438-2		Group 1 and 2 : Grade 5 Group 3 : Grade 5
Thermal resistance		EN 12664	< 0.15 m ² K/W	0.041 m ² K/W

technical data sheet

EN

Environment

property	test method	min. req.	result
Indoor air certifications/labels			Phthalate free, IAC Gold, A+
REACH			Compliant
TVOC (28 days)	EN 16516		< 5 µg/m³
Recycled content			29 %
Release of heavy metals & specific elements	EN 12149		ND
Release of vinyl chloride monomer	EN 12149		ND
Formaldehyde emission			
CE-Marking - EN 15102	 EN 12149	≤ 0.120	ND
REACH Annex XVII Entry 77	EN 16516	< 0.080	< 0.003 mg/m³

Cleaning and maintenance instructions: www.lamett.eu

