

technical data sheet

EN

Product specifications

Rigid Core SPC	EN 15102	DoP WPB2026
Size	Tile	389 x 778 x 4 mm
	Box	8 tiles / 2.421 m ² / 19.95 kg
	Pallet	36 boxes / 87.156 m ² / 746 kg
Density	EN ISO 23996	± 2050 kg/m ³
Installation		Tongue & Groove - 4-sided
Bevel		Painted bevel
Different tiles		3
Texture		Stone Structure
Finish		Standard Gloss (5-8%)
Coating		Antimicrobial UV
Surface layer		Not applicable
Warranty conditions	Residential warranty	15 years
	Commercial warranty	10 years

Product properties

property		test method	min. req.	result
Reaction to fire		EN 13501-1		B-s2, d0
Dimensional stability		EN ISO 23999	≤ 0.15 %	0.03 %
UV resistance		EN ISO 105-B02	≥ 6	6
Scratch resistance		EN 16094	≤ MSR-A5 / ≤ MSR-B5	MSR-A1 MSR-B4
Stain resistance		EN 438-2		Group 1 and 2 : Grade 5 Group 3 : Grade 5
Thermal resistance		EN 12664	< 0.15 m ² K/W	0.039 m ² K/W

technical data sheet

EN

Environment

property	test method	min. req.	result
Indoor air certifications/labels			Phthalate free, IAC Gold, A+
REACH			Compliant
TVOC (28 days)	EN 16516		< 5 µg/m³
Recycled content			29 %
Release of heavy metals & specific elements	EN 12149		ND
Release of vinyl chloride monomer	EN 12149		ND
Formaldehyde emission			
CE-Marking - EN 15102	 EN 12149	≤ 0.120	ND
REACH Annex XVII Entry 77	EN 16516	< 0.080	< 0.003 mg/m³

Cleaning and maintenance instructions: www.lamett.eu

