

New York 190 PEFC

technical data sheet

EN

Product specifications

Three-layer parquet	EN 13489	DoP PQ2024-13
Size	Plank	190 x 680-1900 x 14(3) mm
	Box	8 planks / 2.888 m ² / 21.66 kg
	Full planks	7
	Pallet	45 boxes / 129.96 m ² / 1005 kg
Density	EN 323	± 500 kg/m ³
Installation		Drop Lock
Top layer		European oak (Quercus robur)
Core		Spruce (Picea abies)
Counter balance		Spruce (Picea abies)
Grading		Rustic A+
Texture		Slightly Brushed
Bevel		4V
Gloss level at 60°		5-7 %
Finishing		Matt Lacquer
Warranty conditions	Residential warranty	20 years
	Commercial warranty	upon request
Use class	EN 13489	Class 23 Moderate commercial use



Empty fields indicate variations between the colors within the collection. Please refer to the table below for specific data per color.

Variables within the collection

Article Code	Colour	Finish	Texture
NEW 190-110-PEFC	110 - Natural	UV Matte Lacquer	Slightly Brushed
NEW 190-1817-PEFC	1817 - Invisible	UV Matte Lacquer	Slightly Brushed
NEW 190-1819-PEFC	1819 - Sunset	UV Matte Lacquer	Slightly Brushed

New York 190 PEFC

technical data sheet

EN

Product properties

property		test method	min. req.	result
Indoor air certifications/labels				A
Reaction to fire		EN 13501-1		Dfl-s1
Slip resistance		CEN/TS 15676		USRV 42
Pentachlorophenol content		CEN/TR 14823	< 5 ppm	Does not contain pentachlorophenol
Underfloor heating		EN 12664	R < 0.15 m²K/W	R = 0.11 m²K/W OK (max +28°C) + glued
Biological durability				Class 1

Formaldehyde emission

CE-Marking - EN 14342		EN 717-1	≤ 0.124 mg/m³	E1
REACH Annex XVII Entry 77		EN 717-1	< 0.062 mg/m³	0.025 mg/m³



New York 190 PEFC

Rustic A+
EN

Grading description

Texture	Slightly Brushed
Grading	Rustic
Colour variation	Low - Medium
Sound knots	Allowed unlimited; $\varnothing \leq 20$ mm
Unsound knots	$\varnothing \leq 12$ mm
Sapwood	Allowed unlimited if colour matches plank
End crack	Allowed; filled; width ≤ 50 mm; length ≤ 100 mm
Surface crack	Allowed; filled; width ≤ 50 mm; length ≤ 150 mm
Insect hole	Not allowed
Decay	Not allowed
Blue/yellow stain	Not allowed
Sound heart	Allowed unlimited
Machine marks	Not allowed



This picture is an indication of the grading as described.

Grading description – 2 criteria

Knots

Scale from (rigid) parquet without knots up to planks with more and larger knots



Colour variation

From little colour variation/sapwood to bigger colour variation/sapwood



Cleaning and maintenance instructions: www.lamett.eu